



GP 2500A

Portable Premium Generators (2500 - 9700 W)



Dependable portable power

This lightweight, versatile generator is ideal for smaller jobs. Its durable and compact size offers dependable high performance power with unmatched tool starting ability and voltage regulation. Premium components provide long, trouble-free operation.

- A unique step-start generator technology with AVR (automatic voltage regulation) and separate excitation winding delivers best in class tool starting and voltage regulation.
- A super quiet muffler allows for versatile operation.
- Full wrap around frame with dual cross-member support, high impact polyethylene fuel tank and heavy duty shock mounting combine to provide outstanding impact protection.
- Honda engine with low oil shut down.
- Fully compliant with EPA evaporative emissions regulations



Technical specifications

Portable Premium Generators

Dimensions

| | |
|------------------------------|--------------------------|
| L x W x H Overall | 22.25 x 17.125 x 17.5 in |
| L x W x H Shipping | 23.25 x 17.625 x 19.5 in |
| Weight Dry | 98 lb |
| Operating weight with Fuel | 110 lb |
| Shipping weight without Fuel | 103 lb |

Electrical system

| | |
|-------------------------------------|---------------------|
| Electrical power Maximum Output | 2,500 W |
| Electrical power Continuous Power | 2,250 W |
| Voltage AC - 1 Phase | 120 V |
| Current AC - 1 Phase | 18.8 A |
| Circuit breaker AC - 1 Phase 1 Pole | 20 A |
| Frequency | 60 Hz |
| Power factor | 1 cos Φ 1~ |
| Receptacles AC Outlet | 125V,20A Duplex GFI |
| Receptacles AC Outlet | 125V,20A Duplex |
| Generator model | AVR with Brushes |
| Generator insulation (class) Class | B |

Engine / Motor

| | |
|-----------------------------|----------------------|
| Engine / Motor manufacturer | Honda GX160UT2 |
| Engine / Motor | Recoil |
| Fuel type | Gasoline |
| Cylinder | 1 |
| Displacement | 9.95 in ³ |
| Operating performance | 4.8 hp |
| RPM / speed Operating | 3,600 rpm |
| Power Rating Specification | SAE J1349 |
| Fuel consumption | 0.46 US gal/h |
| Tank capacity Fuel | 3 US gal |
| Tank capacity Oil | 0.65 US qt |



Runtime

6.6 h

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2014 Wacker Neuson SE.