

SPECIFICATION DATA SHEET | MODEL : H10ART-EB








The Abbi H10ART-EB is a transportable fuel tank with a fully galvanized trailer that allows you to refuel equipment easily on your jobsite. With a large lockable equipment cabinet and double walled design, the Abbi is your safe and easy-to-use mobile refueler.

10UCA-EB TRAILER

- Main Frame:** 5" structural channel with 4" structural channel cross members.
- Tongue & Coupler:** Continuation of main frame with height adjustable 2 5/16" ball hitch.
- Platform:** on front and rear of trailer for easy tank access
- Tongue Jack:** 5000 lb. swivel leg, top wind jack.
- Suspension:** Single 3500 lb. torsion axles w/ 5 bolt hubs.
- Brakes:** 10" x 2 1/4" electric on all wheels with re-charging break-away system.
- Tires:** ST215/75R14C on 5 bolt galvanized spoke wheel.
- Lights:** Sealed LED lights
- Trailer Finish:** Hot-dipped galvanized

Abbi 10ART

-  **Transportable.** The Abbi is Transport Canada approved for transport when full. Full load lifting eyes, internal baffles and forklift pockets provide secure and reliable mobility by crane or by forklift to or onsite.
-  **Secure.** The large lockable equipment cabinet is capable of housing and protecting a variety of pumps and hose reels. The secure hose access ports enable fueling while the cabinet is locked. This cabinet captures spills and protects your equipment from theft or damage.
-  **Accessible.** Access manway enables easy access to the inner tank for routine cleaning and maintenance.
-  **Innovative Design.** The unique shape of the has a lower center of gravity which means safer and more reliable mobility.
-  **Environmentally Safe.** Double-walled, 110% containment eliminates the need for spill pans.

SPECIFICATIONS

Standard Tank Fittings: High accuracy contents gauge; 3" Fill point; 2" Fusible link fill port; 1" pump feed; Optional generator feed and return ports (1 set); Pressure/vacuum vent; Pump bracket; Breather vent, 10UCA-EB (highway approved UniChassis trailer).
 Optional Tank Fittings: Complete transfer pump kits; Water & particulate filter kits; (1) set of feed & return blocks; Fuel hose & quick couplers; Hose reel

Capacity Litres: 1,220 (brim-fill); 950 (safe-fill); 1,000 (optimum)	Tank and Trailer Weight Empty (lbs/kg): 1,821 lbs (826kg)
Capacity US Gallons: 322 (brim-fill); 251 (safe-fill); 264 (optimum)	Tank and Trailer Weight Full (lbs/kg): 4,026 lbs (1,827kg)
Dimension Length (mm/in): 3628 mm/ 142.8"	Approvals: UL 142, ULC-S601-07, UN DOT,
Dimension Width (mm/in): 1905 mm/ 75"	Transport Canada, NFPA 30, PPG2
Dimension Height (mm/in): 1626 mm/ 64"	

