



FVO-400



FVNP-400

| Model | FVO-400 Oil | FVOHC-400 Oil | FVNP-400 Dual Fuel |
|-------------------------------------|--|--|---|
| Heat Capacity | up to 390,000 btuh | up to 390,000 btuh | 390,000 btuh |
| Fuel Tank Capacity | 42 US gallons | 42 US gallons | External |
| Operating Time/ Fuel Consumption | 14 hours 2.81 GPH | 14 hours 2.81 GPH | Propane - 4.26 GPH Natural Gas - 390 CFH |
| L x W x H | 70" x 29" x 52" | 70" x 29" x 52" | 70" x 29" x 47" |
| Heat Exchanger | 16 gauge 304 Stainless Steel | 16 gauge 304 Stainless Steel | 16 gauge 304 Stainless Steel |
| Fan Motor | 3/4 HP @ 1,725 rpm 2,500 CFM | 1-1/2 HP @ 3,450 rpm 3,000 CFM | 3/4 HP @ 1,725 rpm 2,500 CFM |
| Ignition | Direct Spark Ignition | Direct Spark Ignition | Direct Spark Ignition |
| Nozzle Size / Gas Pressure | 2.00 x 60B @ 170 PSI | 2.00 x 60B @ 170 PSI | Propane - 1.5" WC Natural Gas - 2.0" WC |
| Air Outlet (optional) | Two 12" diameter One 16" diameter | Two 12" diameter One 16" diameter | Two 12" diameter One 16" diameter |
| Wheels | Two 16" diameter Pneumatic Tubed Wheels | Two 16" diameter Pneumatic Tubed Wheels | Two 16" diameter Pneumatic Tubed Wheels |
| Power Requirements | 115V/60Hz/1Ph/15Amp | 115V/60Hz/1Ph/20Amp | 115V/60Hz/1Ph/15Amp |
| Approvals | cETLus | cETLus | cETLus |
| Weight | 450 lbs | 450 lbs | 450 lbs |