

Indirect Fired Heater

Part Number: FVO-200RC42

185,000 BTU indirect Fired Oil Heater - Recirculating Hood & 42 US GAL tank

- Proven Riello burner technology including nozzle pre-heater for cold weather start up & upgraded low temperature fuel pump
- Welded 304 stainless steel heat exchanger
- Powerful backward incline blower provides ultra-quiet operation & low amperage, ductable up to 150 ft
- Smart power indicator control verifies proper power supply to the heater
- 16" Flat Free Wheels
- 42 US GAL Built-in fuel tank

Category: Heaters - Indirect

Specifications

Name	Description
Heat Capacity:	185,000 BTU H
Fuel Capacity/Run Time	42 US GAL. / 35 HRS
Power Requirements	115V/15 AMPS (6AMP Draw)
Fan Motor/ Air Circulation	1/2 H.P. / 2,600 CFM
Heat Exchanger	16 Gauge 304 Stainless Steel
Ignition	Direct Spark
Nozzle Size/ Pump Pressure	1.10 x 70A/ 180PSI
Air Outlet	1 x 12" Dia or 1 X 16" Dia
Air Intake	1 x 12" Dia
Wheels	2 x 16" Dia Flat Free
Dimensions / Weight	51.5" x 27" x 48" / 350 LBS.
Approvals	cETLus
Outlet Ducting	FV-HD12 - 12" x 12 FT Hitex Black
Outlet Ducting	FV-HD12X25 - 12" x 25 FT Hitex Black
Outlet Ducting	FV-HDG16 - 16" x 25FT Hitex Black
Intake Ducting	FV-HD12 - 12" x 12FT
Remote Thermostat	FV-THB