

IHS700 Ice Fighter Specifications

| Fuel Type | Natural Gas | Propane | Oil |
|---------------------|--|--|--|
| Heating Capacity | 680,000 BTU/hr | 680,000 BTU/hr | 700,000 BTU/hr |
| Fan Motor | 5hp, 1750 RPM | 5hp, 1750 RPM | 5hp, 1750 RPM |
| Burner Motor | 1/3hp, 3450 RPM | 1/3hp, 3450 RPM | 1/3hp, 3450 RPM |
| Manifold Pressure | 3.7" w.c. | 2.9" w.c. | ----- |
| Maximum Inlet | 14" w.c. | 14" w.c. | ----- |
| Minimum Inlet | 7" w.c. | 7" w.c. | ----- |
| Pump Pressure | ----- | ----- | 140 psig |
| Fuel Consumption | 680 CFH 20.3 USGPH | 267 CFH 8.1 USGPH | ----- 5.0 USGPH |
| Minimum Temperature | - 40 Degrees C / F | - 40 Degrees C / F | - 40 Degrees C / F |
| Approval Agency | CSA | CSA | CSA |
| Overall Dimensions | 35"W x 96"L x 45"H 0.9m x 2.5m x 1.2m | 35"W x 96"L x 45"H 0.9m x 2.5m x 1.2m | 35"W x 96"L x 45"H 0.9m x 2.5m x 1.2m |
| CFM | 4,200 | 4,200 | 4,200 |
| Weight | 1,600lbs. | 1,600lbs. | 1,600lbs. |

| | |
|---|-----------|
| IHS700 Ice Fighter Static Pressure | 4" |
|---|-----------|

IHS700 Ice Fighter Amp Draw

| | |
|----------------|-----------------|
| 230V / 3 Phase | 16 Running Amps |
|----------------|-----------------|

| | |
|--|-------------------|
| | 50 Initial Inrush |
|--|-------------------|

| | |
|----------------------|-----------------|
| Optional Low In-Rush | 30 Initial Rush |
|----------------------|-----------------|

| | |
|----------------|-----------------|
| 230V / 1 Phase | 21 Running Amps |
|----------------|-----------------|

| | |
|--|-------------------|
| | 40 Initial Inrush |
|--|-------------------|

| | |
|----------------|------------------|
| 460V / 3 Phase | 6.5 Running Amps |
|----------------|------------------|

| | |
|--|-------------------|
| | 26 Initial Inrush |
|--|-------------------|

| | |
|----------------|------------------|
| 575V / 3 Phase | 5.5 Running Amps |
|----------------|------------------|

| | |
|--|-------------------|
| | 22 Initial Inrush |
|--|-------------------|

