

Manufacturer	John Deere
Model	17G Tier 4 Final
DRIVELINE	
Emission Rating	Tier 4
Engine Manufacturer	Yanmar
Number Of Cylinders (Per Engine)	3
Displacement, ltr (Inches ³)	0.99 (61)
Rated speed, rpm	2400
Engine Output - Net, kW (hp)	10.8 (14.5)
Track Shoe Width, mm (inches)	230 (9)
DIMENSIONS	
Transport Length, mm (ft/in)	3500 (11 ft 6 in)
Overall Width, mm (ft/in)	980 (3 ft 3 in)
Track Length On Ground, mm (ft/in)	1210 (4 ft)
Undercarriage Overall Length, mm (ft/in)	1570 (5 ft 2 in)
Tailswing Radius, mm (ft/in)	680 (2 ft 3 in)
Ground Clearance, mm (inches)	165 (6)
Dozer Blade Height, mm (inches)	260 (10.2)
Digging Reach - Mono Boom, mm (ft/in)	3810 (12 ft 6 in)
Dig Height - Mono Boom, mm (ft/in)	3540 (11 ft 7 in)
Dump Height - Mono Boom, mm (ft/in)	2510 (8 ft 3 in)
Dig Depth - Mono Boom, mm (ft/in)	2190 (7 ft 2 in)
Standard Dipper, mm (ft/in)	930 (3 ft 1 in)
Capacities	
Fuel Tank, ltr (gallons (US))	20.06 (5.3)
Hydraulic Tank, ltr (gallons (US))	14.01 (3.7)
Voltage, V	12
Number Of Batteries	1
Performance	
Ground Bearing Pressure, kPa (PSI)	26.6 (3.9)
Slew Speed, rpm	9.4
Travel Speed - High, kph (mph)	4.2 (2.6)
Dipper Tearout, kN (lbf)	8.6 (1933)
Bucket Breakout, kN (lbf)	16 (3597)
Main Pumps - Maximum Flow, lt/min (gallons (US) / min)	38.4 (10.2)
Weights	
Operating Weight, kg (lbs)	1720 (3790)